

## **Attacchi con codolo conico**

In acciaio speciale

Per mandrini con innesto conico DIN 238/2

**G 900/1** - Esecuzione **standard**

**G 900/2** - Esecuzione **di precisione** interamente temperata e rettificata



Grandezza	11	21	22	31	32	33	34	41	42	43	44	52	53	54	63	64
<b>Codice</b> <i>G 0900 ....</i>	—	1021	—	1031	1032	1033	1034	—	1042	1043	1044	—	—	—	—	—
<b>G 900/1</b> Cad. €																
<b>Codice</b> <i>G 0900 ....</i>	2011	2021	2022	2031	2032	2033	2034	2041	2042	2043	2044	2052	2053	2054	2063	2064
<b>G 900/2</b> Cad. €																
Attacco 238/1	<b>B 10</b>	<b>B 12</b>	<b>B 12</b>	<b>B 16</b>	<b>B 16</b>	<b>B 16</b>	<b>B 16</b>	<b>B 18</b>	<b>B 18</b>	<b>B 18</b>	<b>B 18</b>	<b>B 22</b>	<b>B 22</b>	<b>B 22</b>	<b>B 24</b>	<b>B 24</b>
Ø max. cono DIN 238	10,095	12,065	12,065	15,733	15,733	15,733	15,733	17,780	17,780	17,780	17,780	21,793	21,793	21,793	23,825	23,825
Cono Morse	1	1	2	1	2	3	4	1	2	3	4	2	3	4	3	4