

ELETTROPOMPA SOMMERSA INOX PER DRENAGGIO STAINLESS STEEL SUBMERSIBLE DRAINAGE PUMP

LIMITI D'IMPIEGO

- Temperatura liquido fino a 35° C
- Profondità d'immersione 5 mt.
- Passaggio solidi - Ø 2 mm
- Livello min. d'asp. - Ø 2 mm

MOTORE

- Protezione amperometrica a riarmo automatico incorporata
- Condensatore permanente inserito
- Isolamento Classe F
- Protezione IP 68

MATERIALI

- Maniglia Polipropilene
- Corpo pompa Acciaio Inox
- Girante Noryl
- Cassa motore Acciaio Inox
- Albero motore Acciaio Inox
- Tenuta meccanica

OPERATING CONDITIONS


- Liquid temperature up to 35°C
- Submersion depth 5 mt.
- Grain size inlet - Ø 2 mm
- Min. suction level - Ø 2 mm

MOTOR

- Built-in overload motor protector with automatic reset
- Permanent split capacitor
- Insulation Class F
- Protection IP 68

MATERIALS

- Handle Moplen
- Pump body Stainless Steel
- Impeller Noryl
- Motor casing Stainless Steel
- Shaft with rotor Stainless Steel
- Mechanical seal



TIPO - TYPE	SDX 350/S
P1	350 W
Voltage	230 V
Frequency	50 Hz
Ampere	1,4 A
Q max.	150 l/1'
H max.	7 m
Dnm	1"1/4