



50 + 400

-20 + +80



Ruote con rivestimento in gomma e flange in acciaio. Anello in gomma piena. Flange in acciaio stampato zinco-cromato. Mozzo su cuscinetti a sfere schermati, gabbie a rulli o boccole autolubrificanti.

| 80x25 | 40 | 37 | | 12 | 8 | | 50 |
|------------|----|----|----|----|----|----|-----|
| 100x30 | 40 | 37 | | 12 | 8 | | 70 |
| 125x37,5** | 50 | 46 | | 15 | 10 | | 100 |
| 125x37,5** | 50 | 46 | | 15 | 10 | | 100 |
| 125x37,5** | | | 43 | | | 15 | 100 |
| 140x37,5** | 50 | 43 | | 15 | 10 | | 115 |
| 150x40** | 50 | 43 | | 15 | 10 | | 135 |
| 160x40 | 58 | 55 | | 20 | 17 | | 150 |
| 180x50 | 58 | 55 | | 20 | 17 | | 170 |
| 200x50 | 58 | 55 | | 20 | 17 | | 205 |
| 225x55 | 58 | 55 | | 20 | 17 | | 250 |
| 250x60 | 75 | 63 | | 25 | 25 | | 300 |
| 280x70** | 75 | 64 | | 25 | 25 | | 385 |
| 300x70** | 75 | 64 | | 25 | 25 | | 400 |